



Safety Data Sheet

Copyright, 2016, 3M Company.

All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

Document group:	10-2819-0	Version number:	6.01
Issue Date:	05/04/2016	Supersedes date:	18/02/2015

This Safety Data Sheet has been prepared in accordance with the Preparation of Safety Data Sheets for Hazardous Chemicals Code of Practice (Safe Work Australia, December 2011)

SECTION 1: Identification

1.1. Product identifier

3M™ Stainless Steel Cleaner & Polish

Product Identification Numbers

61-5000-6132-2 AN-0105-5780-7

1.2. Recommended use and restrictions on use

Recommended use

Metal Polish, Cleans and polishes stainless steel, chrome, aluminum and laminated plastic surfaces.

For Industrial or Professional use only.

1.3. Supplier's details

Address: 3M Australia - Building A, 1 Rivett Road, North Ryde NSW 2113
Telephone: 136 136
E Mail: productinfo.au@mmm.com
Website: www.3m.com.au

1.4. Emergency telephone number

EMERGENCY: 1800 097 146 (Australia only)

SECTION 2: Hazard identification

This product is classified as a hazardous chemical according to the Model Work Health and Safety Regulations, 2011.

Refer to Section 14 of this Safety Data Sheets for product Dangerous Goods Classification.

2.1. Classification of the substance or mixture

Flammable Aerosol: Category 1.
Gas under pressure: Liquefied gas.
Specific Target Organ Toxicity (single exposure): Category 1.

2.2. Label elements

The label elements below were prepared in accordance with the Code of Practice on Preparation of Safety Data Sheets for Hazardous Chemicals (Safe Work Australia, December 2011). This information may be different from the actual product

label.

Signal word

DANGER!

Symbols

Flame | Health Hazard |

Pictograms



Hazard statements

H222	Extremely flammable aerosol.
H280	Contains gas under pressure; may explode if heated.
H370	Causes damage to organs: cardiovascular system

Precautionary statements

General:

P102	Keep out of reach of children.
P103	Read label before use.
P101	If medical advice is needed, have product container or label at hand.

Prevention:

P210	Keep away from heat/sparks/open flames/hot surfaces. - No smoking.
P211	Do not spray on an open flame or other ignition source.
P251	Do not pierce or burn, even after use.
P260	Do not breathe dust/fume/gas/mist/vapours/spray.
P270	Do not eat, drink or smoke when using this product.
P264	Wash thoroughly after handling.

Response:

P307 + P311	IF exposed: Call a POISON CENTRE or doctor/physician.
P321	Specific treatment (see Notes to Physician on this label).

Storage:

P410 + P403	Protect from sunlight. Store in a well-ventilated place.
P410 + P412	Protect from sunlight. Do not expose to temperatures exceeding 50°C.
P405	Store locked up.

Disposal:

P501	Dispose of contents/container in accordance with applicable local/regional/national/international regulations.
------	--

2.3. Other assigned/identified product hazards

3M Intentional misuse by deliberately concentrating and inhaling contents can be harmful or fatal.

2.4. Other hazards which do not result in classification

None known.

SECTION 3: Composition/information on ingredients

This material is a mixture.

Ingredient	CAS Nbr	% by Weight
Water	7732-18-5	40 - 70
White mineral oil (petroleum)	8042-47-5	10 - 30
Isobutane	75-28-5	7 - 13
Sorbitan oleate	1338-43-8	0.5 - 1.5
2-Aminoethanol	141-43-5	0.1 - 1

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation

Remove person to fresh air. Get medical attention.

Skin contact

Wash with soap and water. If you feel unwell, get medical attention.

Eye contact

Flush with large amounts of water. Remove contact lenses if easy to do. Continue rinsing. If signs/symptoms persist, get medical attention.

If swallowed

Rinse mouth. If you feel unwell, get medical attention.

4.2. Most important symptoms and effects, both acute and delayed

See Section 11.1. Information on toxicological effects.

4.3. Indication of any immediate medical attention and special treatment required

Exposure may increase myocardial irritability. Do not administer sympathomimetic drugs unless absolutely necessary.

SECTION 5: Fire-fighting measures

5.1. Suitable extinguishing media

Use a fire fighting agent suitable for the surrounding fire.

5.2. Special hazards arising from the substance or mixture

Closed containers exposed to heat from fire may build pressure and explode.

Hazardous Decomposition or By-Products

Substance

Carbon monoxide.

Carbon dioxide.

Condition

During combustion.

During combustion.

5.3. Special protective actions for fire-fighters

No special protective actions for fire-fighters are anticipated.

Hazchem Code: 2YE

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Evacuate area. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Use only non-sparking tools. Ventilate the area with fresh air. WARNING ! A motor could be an ignition source and could cause flammable gases or vapours in the spill area to burn or explode. Refer to other sections of this SDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment.

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

If possible, seal leaking container. Place leaking containers in a well-ventilated area, preferably an operating exhaust hood, or if necessary outdoors on an impermeable surface until appropriate packaging for the leaking container or its contents is available. Working from around the edges of the spill inward, cover with bentonite, vermiculite, or commercially available inorganic absorbent material. Mix in sufficient absorbent until it appears dry. Remember, adding an absorbent material does not remove a physical, health, or environmental hazard. Collect as much of the spilled material as possible using non-sparking tools. Place in a closed container approved for transportation by appropriate authorities. Clean up residue with water. Seal the container. Dispose of collected material as soon as possible.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Do not use in a confined area with minimal air exchange. Keep out of reach of children. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Do not spray on an open flame or other ignition source. Do not pierce or burn, even after use. Do not breathe dust/fume/gas/mist/vapours/spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Avoid contact with oxidising agents (eg. chlorine, chromic acid etc.)

7.2. Conditions for safe storage including any incompatibilities

Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F. Protect from sunlight. Store in a well-ventilated place. Store away from heat. Store away from acids. Store away from oxidising agents.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational exposure limits

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

Ingredient	CAS Nbr	Agency	Limit type	Additional comments
2-Aminoethanol	141-43-5	ACGIH	TWA:3 ppm;STEL:6 ppm	
2-Aminoethanol	141-43-5	Australia OELs	TWA(8 hours): 7.5 mg/m ³ (3 ppm); STEL(15 minutes): 15 mg/m ³ (6 ppm)	
Isobutane	75-28-5	ACGIH	STEL:1000 ppm	
Natural gas	75-28-5	ACGIH	Limit value not established:	
MINERAL OILS, HIGHLY-REFINED OILS	8042-47-5	ACGIH	TWA(inhalable fraction):5 mg/m ³	A4: Not class. as human carcin
Paraffin oil	8042-47-5	Australia OELs	TWA(as mist)(8 hours):5 mg/m ³	

ACGIH : American Conference of Governmental Industrial Hygienists

AIHA : American Industrial Hygiene Association

Australia OELs : Australia. Adopted National Exposure Standards for Atmospheric Contaminants in the Occupational Environment

CMRG : Chemical Manufacturer's Recommended Guidelines

3M™ Stainless Steel Cleaner & Polish

TWA: Time-Weighted-Average

STEL: Short Term Exposure Limit

CEIL: Ceiling

Sen: Sensitiser

Sk: Absorption through the skin may be a significant source of exposure.

8.2. Exposure controls

8.2.1. Engineering controls

Do not remain in area where available oxygen may be reduced. Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapours/spray. If ventilation is not adequate, use respiratory protection equipment.

8.2.2. Personal protective equipment (PPE)

Eye/face protection

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended:

Safety glasses with side shields.

Select and use eye protection in accordance with AS/NZS 1336. Eye protection should comply with the performance specifications of AS/NZS 1337.

Skin/hand protection

Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing. No chemical protective gloves are required.

Gloves made from the following material(s) are recommended: Nitrile rubber.

Select and use gloves according to AS/NZ 2161.

Respiratory protection

None required.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	Liquid.
Specific Physical Form:	Aerosol
Appearance/Odour	Thick white emulsion citrus odour
Odour threshold	<i>No data available.</i>
pH	9 - 11
Melting point/Freezing point	<i>Not applicable.</i>
Boiling point/Initial boiling point/Boiling range	> 100 °C
Flash point	No flash point
Evaporation rate	<i>No data available.</i>
Flammability (solid, gas)	Not applicable.
Flammable Limits(LEL)	<i>No data available.</i>
Flammable Limits(UEL)	<i>No data available.</i>
Vapour density	<i>No data available.</i>
Density	0.95 g/ml
Relative density	0.92 - 0.98 [<i>Ref Std:WATER=1</i>]
Water solubility	Complete
Solubility- non-water	<i>No data available.</i>

Partition coefficient: n-octanol/water	No data available.
Autoignition temperature	No data available.
Decomposition temperature	No data available.
Viscosity	1,400 - 4,500 mPa-s [Details:For Liquid]
Molecular weight	No data available.
Volatile organic compounds (VOC)	10 - 12 % weight [Test Method:calculated per CARB title 2]
Percent volatile	75 - 80 % weight
VOC less H2O & exempt solvents	265 - 295 g/l [Test Method:calculated per CARB title 2]

SECTION 10: Stability and reactivity

10.1 Reactivity

This material is considered to be non reactive under normal use conditions

10.2 Chemical stability

Stable.

10.3. Conditions to avoid

Heat.
Sparks and/or flames.

10.4. Possibility of hazardous reactions

Hazardous polymerisation will not occur.

10.5 Incompatible materials

Strong oxidising agents.
Strong acids.

10.6 Hazardous decomposition products

<u>Substance</u>	<u>Condition</u>
None known.	

SECTION 11: Toxicological information

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. In addition, toxicological data on ingredients may not be reflected in the material classification and/or the signs and symptoms of exposure, because an ingredient may be present below the threshold for labelling, an ingredient may not be available for exposure, or the data may not be relevant to the material as a whole.

11.1 Information on Toxicological effects

Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

Inhalation

Respiratory tract irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain. May cause additional health effects (see below).

Skin contact

Contact with the skin during product use is not expected to result in significant irritation.

3M™ Stainless Steel Cleaner & Polish**Eye contact**

Contact with the eyes during product use is not expected to result in significant irritation.

Ingestion

Gastrointestinal irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhoea.

Additional Health Effects:**Single exposure may cause target organ effects:**

Cardiac sensitisation: Signs/symptoms may include irregular heartbeat (arrhythmia), faintness, chest pain, and may be fatal.

Toxicological Data

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

Acute Toxicity

Name	Route	Species	Value
Overall product	Dermal		No data available; calculated ATE >5,000 mg/kg
Overall product	Inhalation-Dust/Mist(4 hr)		No data available; calculated ATE >12.5 mg/l
Overall product	Ingestion		No data available; calculated ATE >5,000 mg/kg
White mineral oil (petroleum)	Dermal	Rabbit	LD50 > 2,000 mg/kg
White mineral oil (petroleum)	Ingestion	Rat	LD50 > 5,000 mg/kg
Isobutane	Inhalation-Gas (4 hours)	Rat	LC50 276,000 ppm
Sorbitan oleate	Dermal		LD50 estimated to be > 5,000 mg/kg
Sorbitan oleate	Ingestion	Rat	LD50 > 39,800 mg/kg
2-Aminoethanol	Inhalation-Vapour	official classification	LC50 estimated to be 10 - 20 mg/l
2-Aminoethanol	Dermal	Rabbit	LD50 1,000 mg/kg
2-Aminoethanol	Ingestion	Rat	LD50 1,720 mg/kg

ATE = acute toxicity estimate

Skin Corrosion/Irritation

Name	Species	Value
White mineral oil (petroleum)	Rabbit	No significant irritation
Isobutane	Professional judgement	No significant irritation
2-Aminoethanol	Rabbit	Corrosive

Serious Eye Damage/Irritation

Name	Species	Value
White mineral oil (petroleum)	Rabbit	Mild irritant
Isobutane	Professional judgement	No significant irritation
2-Aminoethanol	Rabbit	Corrosive

Skin Sensitisation

Name	Species	Value
White mineral oil (petroleum)	Guinea pig	Not sensitizing
2-Aminoethanol	Guinea pig	Some positive data exist, but the data are not sufficient for classification

Respiratory Sensitisation

For the component/components, either no data are currently available or the data are not sufficient for classification.

3M™ Stainless Steel Cleaner & Polish

Germ Cell Mutagenicity

Name	Route	Value
White mineral oil (petroleum)	In Vitro	Not mutagenic
Isobutane	In Vitro	Not mutagenic
2-Aminoethanol	In Vitro	Not mutagenic
2-Aminoethanol	In vivo	Not mutagenic

Carcinogenicity

Name	Route	Species	Value
White mineral oil (petroleum)	Dermal	Mouse	Not carcinogenic
White mineral oil (petroleum)	Inhalation	Multiple animal species	Not carcinogenic

Reproductive Toxicity

Reproductive and/or Developmental Effects

Name	Route	Value	Species	Test result	Exposure Duration
White mineral oil (petroleum)	Ingestion	Not toxic to female reproduction	Rat	NOAEL 4,350 mg/kg/day	13 weeks
White mineral oil (petroleum)	Ingestion	Not toxic to male reproduction	Rat	NOAEL 4,350 mg/kg/day	13 weeks
White mineral oil (petroleum)	Ingestion	Not toxic to development	Rat	NOAEL 4,350 mg/kg/day	during gestation
2-Aminoethanol	Dermal	Not toxic to development	Rat	NOAEL 225 mg/kg/day	during organogenesis
2-Aminoethanol	Ingestion	Not toxic to development	Rat	NOAEL 616 mg/kg/day	during organogenesis

Target Organ(s)

Specific Target Organ Toxicity - single exposure

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
Isobutane	Inhalation	cardiac sensitization	Causes damage to organs	Multiple animal species	NOAEL Not available	
Isobutane	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Human and animal	NOAEL Not available	
Isobutane	Inhalation	respiratory irritation	All data are negative	Mouse	NOAEL Not available	
2-Aminoethanol	Inhalation	respiratory irritation	May cause respiratory irritation	Human and animal	NOAEL Not available	

Specific Target Organ Toxicity - repeated exposure

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
White mineral oil (petroleum)	Ingestion	hematopoietic system	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 1,381 mg/kg/day	90 days
White mineral oil	Ingestion	liver immune system	Some positive data exist, but the	Rat	NOAEL 1,336 mg/kg/day	90 days

3M™ Stainless Steel Cleaner & Polish

(petroleum)			data are not sufficient for classification			
Isobutane	Inhalation	kidney and/or bladder	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 4,500 ppm	13 weeks
2-Aminoethanol	Inhalation	liver kidney and/or bladder respiratory system	Some positive data exist, but the data are not sufficient for classification	Multiple animal species	NOAEL 0.656 mg/l	5 weeks
2-Aminoethanol	Ingestion	hematopoietic system liver kidney and/or bladder respiratory system	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL Not available	

Aspiration Hazard

Name	Value
White mineral oil (petroleum)	Aspiration hazard

Exposure Levels

Refer Section 8.1 **Control Parameters** of this Safety Data Sheet.

Interactive Effects

Not determined.

SECTION 12: Ecological information

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. Additional information leading to material classification in Section 2 is available upon request. In addition, environmental fate and effects data on ingredients may not be reflected in this section because an ingredient is present below the threshold for labelling, an ingredient is not expected to be available for exposure, or the data is considered not relevant to the material as a whole.

12.1. Toxicity**Acute aquatic hazard:**

Not acutely toxic to aquatic life by GHS criteria.

Chronic aquatic hazard:

Not chronically toxic to aquatic life by GHS criteria.

No product test data available.

Material	CAS Number	Organism	Type	Exposure	Test endpoint	Test result
2-Aminoethanol	141-43-5	Water flea	Experimental	21 days	NOEC	0.85 mg/l
2-Aminoethanol	141-43-5	Water flea	Experimental	48 hours	EC50	97 mg/l
2-Aminoethanol	141-43-5	Green Algae	Experimental	72 hours	EC50	2.5 mg/l
2-Aminoethanol	141-43-5	Goldfish	Experimental	96 hours	LC50	170 mg/l

3M™ Stainless Steel Cleaner & Polish

Isobutane	75-28-5		Data not available or insufficient for classification			
White mineral oil (petroleum)	8042-47-5	Water flea	Experimental	21 days	NOEC	>100 mg/l
White mineral oil (petroleum)	8042-47-5	Bluegill	Experimental	96 hours	Lethal Level 50%	>100 mg/l
Sorbitan oleate	1338-43-8	Rainbow trout	Experimental	96 hours	LC50	>100 mg/l

12.2. Persistence and degradability

Material	CAS Number	Test type	Duration	Study Type	Test result	Protocol
Isobutane	75-28-5	Experimental Photolysis		Photolytic half-life (in air)	13.7 days (t _{1/2})	Other methods
Sorbitan oleate	1338-43-8	Estimated Biodegradation	28 days	BOD	81 % weight	OECD 301C - MITI test (I)
White mineral oil (petroleum)	8042-47-5	Experimental Biodegradation	28 days	CO ₂ evolution	0 % weight	OECD 301B - Modified sturm or CO ₂
2-Aminoethanol	141-43-5	Experimental Biodegradation	14 days	BOD	83 % weight	OECD 301C - MITI test (I)

12.3 : Bioaccumulative potential

Material	CAS Number	Test type	Duration	Study Type	Test result	Protocol
White mineral oil (petroleum)	8042-47-5	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Sorbitan oleate	1338-43-8	Estimated Bioconcentration		Bioaccumulation factor	9.8	Estimated: Bioconcentration factor
Isobutane	75-28-5	Experimental BCF - Other		Bioaccumulation factor	1.97	Other methods
2-Aminoethanol	141-43-5	Experimental Bioconcentration		Log Kow	-1.31	Other methods

12.4. Mobility in soil

Please contact manufacturer for more details

12.5 Other adverse effects

No information available.

The surfactant(s) contained in this preparation comply with the biodegradability criteria as laid down in Regulation (EC) No.648/2004 on detergents.

SECTION 13: Disposal considerations**13.1. Disposal methods**

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Incinerate in a permitted waste incineration facility. Facility must be capable of handling aerosol cans.

SECTION 14: Transport Information

Australian Dangerous Goods Code (ADG) - Road/Rail Transport

UN No.: UN1950

Proper shipping name: AEROSOLS

Class/Division: 2.1

Sub Risk: Not applicable.

Packing Group: Not applicable.

Hazchem Code: 2YE

IERG: 49

International Air Transport Association (IATA) - Air Transport

UN No.: UN1950

Proper shipping name: AEROSOLS, FLAMMABLE

Class/Division: 2.1

Sub Risk: Not applicable.

Packing Group: Not applicable.

International Maritime Dangerous Goods Code (IMDG)- Marine Transport

UN No.: UN1950

Proper shipping name: AEROSOLS

Class/Division: 2.1

Sub Risk: Not applicable.

Packing Group: Not applicable.

Marine Pollutant: Not applicable.

Special Instructions: Limited quantity may apply

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Australian Inventory Status:

The chemical components contained within this product are listed on the Australian Inventory of Chemical Substances and are in compliance with the requirements of the Industrial Chemicals (Notification and Assessment) Act 1989 as amended.

Poison Schedule: This product has not been assessed for poisons scheduling as the product is intended for industrial and professional use only.

SECTION 16: Other information

Revision information:

Conversion to GHS format SDS.

DISCLAIMER: The information on this Safety Data Sheet is based on our experience and is correct to the best of our knowledge at the date of publication, but we do not accept any liability for any loss, damage or injury resulting from its use (except as required by law). The information may not be valid for any use not referred to in this Safety Data Sheet or use of the product in combination with other materials. For these reasons, it is important that customers carry out their own test to satisfy themselves as to the suitability of the product for their own intended applications.

Greenguard® is a United States based program. The 'Low VOC' reference related to United States Federal and State regulations exemptions for some solvents.

3M Australia SDSs are available at www.3m.com.au